

## SPRINT 125 ABS





## SPRINT 125 ABS

SPECIFICATIONS	
Engine	Single cylinder 4-stroke, 3 valves, i-get
Engine capacity	124 cc
Bore x stroke	52 mm x 58.6 mm
Max Power at the crank shaft	8.1 kW - 11 HP - at 8,000 rpm
Max Torque	10.4 Nm at 6,750 rpm
Consumption	40 km/l
CO <sub>2</sub> emissions compliance	60 g/km
Fuel system	Electronic injection
Cooling	Forced air
Starter	Electric
Gearbox	CVT continuously variable transmission with torque server
Clutch	Automatic centrifugal dry clutch with vibration dampers
Load-bearing structure	Sheet steel body with welded reinforcements
Front suspension	Single-sided link arm with coil spring and hydraulic monoshock absorber
Rear suspension	Coil spring with preload adjustable to 4 positions and hydraulic monoshock absorber
Front brake	Ø 200 mm stainless steel disc with hydraulic control
Rear brake	Ø 140 mm drum mechanically operated
ABS system	ABS only on the front wheel
Front tyre	Tubeless 110/70 - 12"
Rear tyre	Tubeless 120/70 - 12"
Length/Width/Wheelbase	1,870 / 735 / 1,340 mm
Seat Height	790 mm
Fuel tank capacity	8 litres
Emissions compliance	Euro 5

## COLOURS



